

99A00-2

DISCONTINUED

OmniTouch 7 Touchscreen, Power over Ethernet, Facilitates complete control over subsystems, Black.

Capacitive touch, glass front Touchscreen designed for use with any one of our three automation platforms, either Omni, BitWise, or Lumina Gateway utilizing one hardware SKU and multiple firmware versions. Features a 7" diagonal viewing area at 800x480 resolution for control of your security, energy, and/or entertainment settings.



UPC Code : 872257009439

Country Of Origin : Taiwan

RoHS Compliant : Yes

Technical Information

Product Features

Product Type : Interface

Product Line : BitWise

Features and Benefits

- Change firmware to either connect to Omni, Gateway, or BitWise platform.
- Omni version updated! New Shades and Support Icons on Main Menu. Camera Pop-Up on Event. All Off Lighting. And More!
- Lumina Gateway and Omni: Access dozens of thermostats including humidity settings
- Lumina Gateway and Omni: Control lighting loads including outdoor signage
- Lumina Gateway and Omni: Control ventilation and window coverings
- Omni: View crisp IP surveillance video footage without any additional hardware. MJPEG and JPEG IP Cameras can be viewed, as well as analog with an analog to IP converter
- Omni: User-selectable language for Omni systems: English, Spanish, French and Italian
- Omni: Arm or Disarm your security system or alert emergency personnel
- Omni: Quickly check whether all doors are locked and either unlock or lock any door from one menu
- Omni: Quick glance LED on the top right corner is green when security is disarmed and red when armed
- Omni: Utilize slider bars to adjust lighting load levels from 0 to 100%
- Omni: Control Leviton's Hi-Fi 2 Distributed Audio System or a compatible system from a Connectivity Partner
- Large approx 7" diagonal viewing area with minimal plastic surround available in Black or White
- 7.25"x5.125"x0.55" on exterior wall surface, and 6"x4"x1" behind surface of wall
- Glass front capacitive touchscreen at 800x480 resolution
- PoE connection provides all power and communication
- Firmware updates via Ethernet
- 2 watt mono digital amplifier and speaker
- Two digital MEMS microphones for improved noise and echo cancellation

- Light sensor allows automatic dimming of display backlight

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

